

PROFESSIONAL DVR

❖ MODEL : SVS-800



❖ FEATURE :

- ◆ H.264 high profile video recorder
- ◆ Real Full HD display (HD Output)
- ◆ Live & Playback in full HD display
- ◆ Able to display 1CH playback in live view mode simultaneously
- ◆ Individual recording set up
- ◆ Support 1 HDD (up to 6 TB for per disk)
- ◆ Multiple Recording Mode
- ◆ RS485 port for PTZ control
- ◆ Free ISS Management software and DDNS server
- ◆ Free Mobile (Windows, Mac, Iphone, Android)

❖ SPECIFICATIONS :

MODEL		SVS-800
Compression Algorithm		H.264
HDD Interface		1ea x SATA
System		Embedded Linux
Video	Input	8 BNC
	Looping	2 x Loop out ports (D-Sub up to 16ch, Optional cable required)
Video Mode		NTSC / PAL Auto Detection
Display Speed (NTSC / PAL)		480 / 400 fps @ 960H
Screen Split		1,4,9
Video	Monitor	2ea x Main Monitor (HD Output , Composite) 1 x Analogue Spot out
	VGA Resolution	1920x1080P, 1280x720P, 1280x1024, 1024x768
Recording Speed (NTSC / PAL)	480x240/ 288	240 / 200 fps
	960x240/ 288	240 / 200 fps
	960x480/ 576	240 / 200 fps
Recording Resolution		NTSC : 480x240, 960x240, 960x480, PAL : 480x288, 960x288, 960x576
Recording Modes		Time-Lapse, Event, Pre-Event, Post-Event, Instant(Panic) Record
Play back & Search	Speed	x1/32,x1/16,x1/8,x1/4, x1/2 x1, x2, x4, x8, x16, x32
	Function	1,4,9,1+5,1+7ch (Multi-Channel Playback) Date/Time, Record Table, Calendar, Event preview, Bookmark, Play from Search, System Log
Audio Input / Output		In : 1xPhone Jack/ Out : 1xPhone Jack
Alarm Input / Relay Output		4 x In / 1 x Relay Out
P/T/Z Control and Port		Virtual Joy-Stick control on screen (by mouse) RS485 Port 1EA(PTZ, Keyboard Controller)
LAN		1x10/ 100/1000Mbps Ethernet
Network Transmission	function	240/200 fps @ 960*480(576), 240/200 fps @480*240(288)
		Video Dual-Stream (Local Recording & Network Transmission)
		Live Monitoring, Remote Playback and File Backup (Triplex-on-Remote)
		Remote & E-Mail Notication with JPEG, Remote System Reboot byClient(ACS&CMS)
Mobile Device Support		Android, iPhone, Kindlere
Remote PTZ Control		Pan / Tilt / Zoom / Focus / Iris
Remote Management		CMS, Live Monitoring, Playback & System Conguration
Backup Device External		Local Backup by USB Memory Stick(2ea), Network Backup by CMS Support
System Operation		USB Mouse, Front Keys
Temperature & Humidity		Storage -20~60°C / 20~95% RH, Operating 5~40°C / 20~80% RH
Certication		CE, FCC, WEEE, RoHS
Dimension(W x H x D)		280 x 48 x 245